

## ***System Specifications and Features***

### **Skid**

- Forklift access
- Insulated weatherproof design
- Spring mounted heaters provide constant thermal cylinder contact
- Designed to fit "ton" cylinders and other sizes
- Exhaust lip provided to exhaust nozzle area
- System designed for easy installation/removal of gas cylinders
- No electrical contact is made with cylinder.
- Professional and clean powder coated panel finish

### **Dimensions**

- Custom designed to fit large capacity containers.  
DOT-3a-1800/2400, 24" o.d.  
86" long 28" wide x 33" high

### **Approvals**

- CSA 200043
- CE

### **Control System**

- 380V to 480V 3PH 50/60 HZ 30 A
- Insulated weatherproof design
- Regulates heater with PID controller based on part (cylinder) temperature and set point
- Limits heater upper temperature thereby eliminating the risk of overheating the cylinder. (125°F)
- EMI Filter
- GFCI Protection
- Redundant Vessel Over Temperature Shutdown

### **System Performance**

- Maximum heat input – 9.6 kW @460VAC (Dependent on regulated temperature)
- Minimum ambient temperature recommended for operation – 0°F

### **Options**

- Integrated weighing and inventory management system
- Climate Control
- Exhaust Hood

***Accurate Gas Control Systems, Inc.***

2825 South Rodeo Gulch Road#1 Soquel, California 95073 (831) 462-0500 FAX: (831) 462-0507 Email: [agcs@accurategas.com](mailto:agcs@accurategas.com)

